



日式B1168吊环螺栓  
***JIS B 1168 Eye Bolt***

- Forged carbon steel - Normalizing
- Electric plated or Self colored
- Forged eye bolt meet the performance requirements of JIS B 1168.
- Cast stainless steel

Size		Dimension(in)						S.W.L.	Weight
MM	INCH	A	B	C	D	H	L	(Ton)	(lbs)
M8	5/16U	1.28	0.79	0.25	0.63	1.31	0.59	0.08	0.09
M10	3/8U	1.61	0.98	0.31	0.79	1.63	0.71	0.15	0.15
M12	1/2U	1.97	1.18	0.39	0.98	2.01	0.87	0.22	0.31
M16	5/8U	2.36	1.38	0.49	1.18	2.36	1.06	0.45	0.57
M20	3/4U	2.83	1.57	0.63	1.38	2.8	1.18	0.63	0.95
M22	7/8U	3.15	1.73	0.71	1.57	3.11	1.38	0.79	1.23
M24	1U	3.54	1.97	0.79	1.77	3.54	1.5	0.95	1.87
M30	1-1/4U	4.33	2.36	0.98	2.36	4.33	1.77	1.5	3.74
M36	1-1/2U	5.24	2.76	1.24	2.76	5.18	2.17	2.3	6.61
M42	1-3/4U	5.94	3.15	1.4	3.15	5.93	2.56	3.4	9.91
M48	2U	6.69	3.54	1.57	3.54	6.69	2.76	4.5	14.76

<b>M64</b>	<b>-</b>	<b>8.27</b>	<b>4.33</b>	<b>1.97</b>	<b>4.33</b>	<b>8.27</b>	<b>3.54</b>	<b>9</b>	<b>24.89</b>
<b>M80</b>	<b>-</b>	<b>10.47</b>	<b>5.51</b>	<b>2.48</b>	<b>5.12</b>	<b>10.35</b>	<b>4.13</b>	<b>15</b>	<b>-</b>
<b>M90</b>	<b>-</b>	<b>11.89</b>	<b>6.3</b>	<b>2.8</b>	<b>5.91</b>	<b>11.85</b>	<b>4.72</b>	<b>18</b>	<b>-</b>
<b>M100</b>	<b>-</b>	<b>13.39</b>	<b>7.09</b>	<b>3.15</b>	<b>6.69</b>	<b>13.98</b>	<b>5.12</b>	<b>20</b>	<b>-</b>